ThermoAlert...

Dual alarm electronic temperature indicator

Validated time-temperature alarm indicator for in-transit monitoring

Sensitech's ThermoAlert_™ dual alarm electronic temperature indicator monitors the last-mile distribution segment for pharmaceuticals and biologics, providing product "accept/ reject" information relative to transit and storage temperature conditions. The ThermoAlert indicator is a single-use, factory programmed, disposable device, deployed at the manufacturer or distributor and evaluated at the receiving site.

- Two factory-set single-event or cumulative time/temperature alarms; high (>) and low (<)
- Custom time and temperature alarm settings tailored to specific product needs
 - Temperature threshold value from -20°C to +50°C (-4°F to +122°F)
 - Time threshold value from 0 minutes to 30 days
- Monitors temperature sensitive shipments up to 30 days
- Clear digital display presents unequivocal results of alarm conditions
- NIST® traceable calibration verifies device accuracy
- Field activated via integrated start button; no pre-conditioning or controlled shipping/storage conditions required





ThermoAlert.

	Specifications
Operating Range	-20°C to 50°C (-4°F to 122°F)
Operating Life	Minimum 30 days
Shelf Life	12 months prior to activation
Accuracy	$\pm 0.5^{\circ}$ C accuracy from -10°C to 25°C $\pm 1.0^{\circ}$ F from 14°F to 77°F $\pm 1.0^{\circ}$ C from -20°C to -10°C $\pm 2.0^{\circ}$ F from -4°F to 14°F $\pm 1.0^{\circ}$ C from 25°C to 50°C $\pm 2.0^{\circ}$ F from 77°F to 122°F
Alarm Settings	One high alarm (>), One low alarm (<) Single event or cumulative -20°C to 50°C, 0.1°C resolution Up to 30 days, 1 minute resolution
Startup Delay	0 to 255 minutes
Measurement Interval	1-minute
Display	6-Icon LCD (✓, X, HI, LO,♥,
Size/Weight	47.6mm x 38.1mm x 11.1mm, 14.2g 1-7/8" x 1-1/2" x 7/16", 0.5 oz
Enclosure Protection	IP 54 (per IEC 529)
Activation	Momentary switch, 3 second contact
Certification	FCC, CE



ThermoAlert Operation

The ThermoAlert indicator is supplied with two factory set time/temperature alarms configured to your specifications.

An alarm is activated if the temperature exceeds the specified temperature threshold for the time period established for each alarm.



No activated alarms



Low alarm activated



High alarm activated



High and low alarm activated

Sensitech Inc. is focused on delivering supply chain visibility solutions that track, monitor and protect products for global leaders in the food, life sciences, consumer goods, and industrial markets. Our solutions are focused in three key areas: quality and compliance, supply chain security, and logistics performance management. Quality and compliance solutions address temperature-sensitive, complex supply chains focused on delivering the highest quality possible, while our supply chain security solutions help to mitigate risks associated with theft, diversion and chain of custody. Sensitech's logistics performance solutions deliver origin-to-destination, real-time transparency to any in-transit journey. Sensitech Inc. is an ISO 9001:2015 company, headquartered in Beverly, Mass., with over 35 sales, service and distribution locations around the world. Sensitech is a Carrier company, a leading provider of heating, air conditioning and refrigeration systems, building controls and automation, and fire and security systems leading to safer, smarter, sustainable and high-performance buildings. NIST is a registered trademark of The National Institute of Standards and Technology Agency of the United States Government. Unless otherwise indicated, all trademarks and service marks are the property of Sensitech Inc. Visit www.sensitech.com for additional information. ©2020 Carrier. All Rights Reserved.

Sensitech Inc. • Global Headquarters • 800 Cummings Center • Suite 258X • Beverly, MA 01915-6197 1-800-843-8367 • +1-978-927-7033 • Fax: +1-978-921-2112 • sensitech.clientservices@carrier.com



08/20

sensitech.com